

# ASRock M.2 (Key E) Socket Support List

System Interface Type: PCIe WiFi Module

Board Form Factor: M.2 2230

Vendor	Model	System Interface Type	Antenna	
<b>Intel</b>	Intel® Wireless-AC 9260	Wi-Fi (PCIe), BT (USB)	2T2R	<a href="#">Link</a>
<b>Intel</b>	Intel® Dual Band Wireless-AC 3168	Wi-Fi (PCIe), BT (USB)	1T1R	<a href="#">Link</a>
<b>Intel</b>	Intel® Wi-Fi 6 AX200	Wi-Fi (PCIe), BT (USB)	2T2R	<a href="#">Link</a>
<b>Intel</b>	Intel® Wi-Fi 6E AX210	Wi-Fi (PCIe), BT (USB)	2T2R	<a href="#">Link</a>
<b>AMD</b>	AMD RZ616 Wi-Fi 6E	Wi-Fi (PCIe), BT (USB)	2T2R	<a href="#">Link</a>
<b>AMD</b>	AMD RZ608 Wi-Fi 6E	Wi-Fi (PCIe), BT (USB)	2T2R	<a href="#">Link</a>
<b>Intel</b>	Intel® Killer™ Wi-Fi 6 AX1650 (x/w)	Wi-Fi (PCIe), BT (USB)	2T2R	<a href="#">Link</a>